

1700/40 200'SF



3M

Authorized Distributor

Part Number: 1700/40 200'SF

Manufacturer 3M

Description CBL RIBN 40COND TWIST-PAIR 200'

Data sheet:  1700 Series  Internal Wiring Guide

RoHS Status: Lead free / RoHS Compliant








Ship From: Hong Kong

Shipment Way: DHL/Fedex/TNT/UPS/EMS

Images are for reference only.  
See Product Specifications for product details.  
Buy 1700/40 200'SF with confidence from Component-World.HK, 1 Year Warranty

Request For Quotation

| PRODUCT PARAMETER                                                                                                                                                                                                                                                                                                                                                               |                                 |                                 |                                                                                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|---------------------------------|--------------------------------------------------------------------------------------------------------------|
| Part Number                                                                                                                                                                                                                                                                                                                                                                     | 1700/40 200'SF                  | Manufacturer                    | 3M                                                                                                           |
| Description                                                                                                                                                                                                                                                                                                                                                                     | CBL RIBN 40COND TWIST-PAIR 200' | Lead Free Status / RoHS Status  | Lead free / RoHS Compliant                                                                                   |
| Quantity Available                                                                                                                                                                                                                                                                                                                                                              | 321 pcs                         | Data sheet                      | 1700 Series<br>Internal Wiring Guide                                                                         |
| Category                                                                                                                                                                                                                                                                                                                                                                        | Cables, Wires                   | Wire Gauge                      | 28 AWG                                                                                                       |
| Voltage                                                                                                                                                                                                                                                                                                                                                                         | 300V                            | Shielding                       | Unshielded                                                                                                   |
| Series                                                                                                                                                                                                                                                                                                                                                                          | 1700                            | Ribbon Width                    | 2.000" (50.80mm)                                                                                             |
| Ribbon Thickness                                                                                                                                                                                                                                                                                                                                                                | 0.080" (2.03mm)                 | Ratings                         | UL Style 20462                                                                                               |
| Pitch                                                                                                                                                                                                                                                                                                                                                                           | 0.050" (1.27mm)                 | Other Names                     | 00051138407759<br>1700/40 200'SF-ND<br>1700/40200'SF<br>80610792089                                          |
| Operating Temperature                                                                                                                                                                                                                                                                                                                                                           | -20°C ~ 105°C                   | Number of Conductors            | 40 (20 Pair Twisted)                                                                                         |
| Moisture Sensitivity Level (MSL)                                                                                                                                                                                                                                                                                                                                                | 1 (Unlimited)                   | Manufacturer Standard Lead Time | 5 Weeks                                                                                                      |
| Length                                                                                                                                                                                                                                                                                                                                                                          | 200.0' (60.96m)                 | Lead Free Status / RoHS Status  | Lead free / RoHS Compliant                                                                                   |
| Jacket Color                                                                                                                                                                                                                                                                                                                                                                    | Multiple                        | Jacket (Insulation) Material    | Poly-Vinyl Chloride (PVC)                                                                                    |
| Insulation Resistance                                                                                                                                                                                                                                                                                                                                                           | 1 GOhms                         | First Conductor Mark            | -                                                                                                            |
| Features                                                                                                                                                                                                                                                                                                                                                                        | -                               | Detailed Description            | Flat Ribbon Cable Multiple 40 (20 Pair Twisted) Conductors 0.050" (1.27mm) Flat Twisted Pair 200.0' (60.96m) |
| Conductor Strand                                                                                                                                                                                                                                                                                                                                                                | 7 Strands / 36 AWG              | Conductor Material              | Copper, Tinned                                                                                               |
| Cable Type                                                                                                                                                                                                                                                                                                                                                                      | Flat Twisted Pair               |                                 |                                                                                                              |
| Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all 3M series electronic components. We have 321 pieces of 3M 1700/40 200'SF in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours.<br>RFQ Email: info@Components-World.com |                                 |                                 |                                                                                                              |

| RELATED PRODUCTS                                                                   |                                                                       |                   |     |
|------------------------------------------------------------------------------------|-----------------------------------------------------------------------|-------------------|-----|
|  | Part#: 1700/40 200<br>Description: CBL RIBN 40COND TWIST-PAIR 200'    | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40BA<br>Description: CBL RIBN 40COND TWIST-PAIR 100'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40EH<br>Description: CBL RIBN 40COND TWIST-PAIR 300'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/34TB 300'<br>Description: CBL RIBN 34COND TWIST-PAIR 300' | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40 100<br>Description: CBL RIBN 40COND TWIST-PAIR 5'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/50 100SF<br>Description: CBL RIBN 50COND TWIST-PAIR 10'   | Manufacturers: 3M | RFQ |
|  | Part#: 1700/34BP<br>Description: CBL RIBN 34COND TWIST-PAIR 100'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40BN<br>Description: CBL RIBN 40COND TWIST-PAIR 300'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40BP<br>Description: CBL RIBN 40COND TWIST-PAIR 100'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/50 100<br>Description: CBL RIBN 50COND TWIST-PAIR 5'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40TB<br>Description: CBL RIBN 40COND TWIST-PAIR 100'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/50 200<br>Description: CBL RIBN 50COND TWIST-PAIR 200'    | Manufacturers: 3M | RFQ |
|  | Part#: 1700/36 100<br>Description: CBL RIBN 36COND TWIST-PAIR 100'    | Manufacturers: 3M | RFQ |
|  | Part#: 1700/34BW<br>Description: CBL RIBN 34COND TWIST-PAIR 100'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/34TB<br>Description: CBL RIBN 34COND TWIST-PAIR 100'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/34TD<br>Description: CBL RIBN 34COND TWIST-PAIR 100'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40TD<br>Description: CBL RIBN 40COND TWIST-PAIR 100'      | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40 100SF<br>Description: CBL RIBN 40COND TWIST-PAIR 5'    | Manufacturers: 3M | RFQ |
|  | Part#: 1700/40 300SF<br>Description: CBL RIBN 40COND TWIST-PAIR 300'  | Manufacturers: 3M | RFQ |
|  | Part#: 1700/36 100SF<br>Description: CBL RIBN 36COND TWIST-PAIR 5'    | Manufacturers: 3M | RFQ |

| Related keywords for 1700/40 200'SF |                            |                         |                                 |
|-------------------------------------|----------------------------|-------------------------|---------------------------------|
| 3M 1700/40 200'SF                   | 1700/40 200'SF distributor | 1700/40 200'SF supplier | 1700/40 200'SF price            |
| 1700/40 200'SF download datasheet   | 1700/40 200'SF datasheet   | 1700/40 200'SF stock    | buy 1700/40 200'SF              |
| 3M 1700/40 200'SF                   | 3M Inc 1700/40 200'SF      | 3M (TC) 1700/40 200'SF  | 3M Touch Systems 1700/40 200'SF |