

2722/16 RD/M



DABURN

Part Number:

2722/16 RD/M

Manufacturer:

Daburn

Description:

TEST LEAD 16AWG 5000V RED 1000'

Data sheet:

 [2722 Series](#)

RoHS Status:

Lead free / RoHS Compliant

Ship From:

Hong Kong


















Shipment Way:

DHL/Fedex/TNT/UPS/EMS

Images are for reference only.
See Product Specifications for product details.
Buy 2722/16 RD/M with confidence from Component-World.HK, 1 Year Warranty

Request For Quotation

PRODUCT PARAMETER			
Part Number	2722/16 RD/M	Manufacturer	Daburn
Description	TEST LEAD 16AWG 5000V RED 1000'	Lead Free Status / RoHS Status	Lead free / RoHS Compliant
Quantity Available	442 pcs	Data sheet	2722 Series
Category	Cables, Wires	Wire Gauge	16 AWG
Voltage	5000V	Series	MIL-I-3930A Type JP
Ratings	-	Other Names	2722/16RD/M W2716R-1000
Operating Temperature	-80°C ~ 80°C	Moisture Sensitivity Level (MSL)	Not Applicable
Manufacturer Standard Lead Time	7 Weeks	Length	1000.0' (304.8m)
Lead Free Status / RoHS Status	Lead free / RoHS Compliant	Jacket Color	Red
Jacket (Insulation) Thickness	0.032" (0.81mm)	Jacket (Insulation) Material	Poly-Vinyl Chloride (PVC)
Jacket (Insulation) Diameter	0.129" (3.28mm)	Features	-
Detailed Description	16 AWG Test Lead Wire 65/34 Red 5000V 1000.0' (304.8m)	Conductor Strand	65/34
Conductor Material	Copper, Tinned	Cable Type	Test Lead
Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Daburn series electronic components. We have 442 pieces of Daburn 2722/16 RD/M in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours. RFQ Email: info@Components-World.com			

RELATED PRODUCTS			
	Part#: 2722/16 YE/M Description: TEST LEAD 16AWG 5000V YEL 1000'	Manufacturers: Daburn	RFQ
	Part#: 2722/18 BU/C Description: TEST LEAD 18AWG 5000V BLUE 100'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 RED Description: TEST LEAD 16AWG 5000V RED 1000'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 BK/M Description: TEST LEAD 16AWG 5000V BLK 1000'	Manufacturers: Daburn	RFQ
	Part#: 2722/18 B/C Description: TEST LEAD 18AWG 5000V BLACK 100'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 WHITE/C Description: TEST LEAD 16AWG 5000V WHITE 100'	Manufacturers: Daburn	RFQ
	Part#: 2722 Description: ELECTRO-FASHION CONDUCTIVE THREA	Manufacturers: Kitronik	RFQ
	Part#: 2722/16 WHITE/M Description: TEST LEAD 16AWG 5000V WHT 1000'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 BU/M Description: TEST LEAD 16AWG 5000V BLUE 1000'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 BK/C Description: TEST LEAD 16AWG 5000V BLACK 100'	Manufacturers: Daburn	RFQ
	Part#: 2722/18 BU/M Description: TEST LEAD 18AWG 5000V BLUE 1000'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 GN/M Description: TEST LEAD 16AWG 5000V GRN 1000'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 YE/C Description: TEST LEAD 16AWG 5000V YEL 100'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 BLACK Description: TEST LEAD 16AWG 5000V BLK 1000'	Manufacturers: Daburn	RFQ
	Part#: 2721976 Description: FUSE BOARD MOUNT 5A	Manufacturers: Phoenix Contact	RFQ
	Part#: 2722/18 B/M Description: TEST LEAD 18AWG 5000V BLK 1000'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 RD/C Description: TEST LEAD 16AWG 5000V RED 100'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 BU/C Description: TEST LEAD 16AWG 5000V BLUE 100'	Manufacturers: Daburn	RFQ
	Part#: 2722/16 GN/C Description: TEST LEAD 16AWG 5000V GREEN 100'	Manufacturers: Daburn	RFQ
	Part#: 2722/18 BLUE/C Description: TEST LEAD 18AWG 5000V BLUE 100'	Manufacturers: Daburn	RFQ

Related keywords for 2722/16 RD/M			
Daburn 2722/16 RD/M	2722/16 RD/M distributor	2722/16 RD/M supplier	2722/16 RD/M price
2722/16 RD/M download datasheet	2722/16 RD/M datasheet	2722/16 RD/M stock	buy 2722/16 RD/M
Daburn 2722/16 RD/M	Daburn Electronics 2722/16 RD/M		