

30-00804



TENSILITY

Part Number: 30-00804

Manufacturer: Tensility International Corporation

Description: CBL 2CON 24AWG RD/BLK 5M

Data sheet:  30-00804 Drawing

RoHs Status: Lead free / RoHS Compliant



Ship From: Hong Kong

Shipment Way: DHL/Fedex/TNT/UPS/EMS

Images are for reference only.  
See Product Specifications for product details.  
Buy 30-00804 with confidence from Component-World.HK, 1 Year Warranty

Request For Quotation

| PRODUCT PARAMETER                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                    |                                |                                                     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|--------------------------------|-----------------------------------------------------|
| Part Number                                                                                                                                                                                                                                                                                                                                                                                                                                   | 30-00804                                                           | Manufacturer                   | <a href="#">Tensility International Corporation</a> |
| Description                                                                                                                                                                                                                                                                                                                                                                                                                                   | CBL 2CON 24AWG RD/BLK 5M                                           | Lead Free Status / RoHS Status | Lead free / RoHS Compliant                          |
| Quantity Available                                                                                                                                                                                                                                                                                                                                                                                                                            | 14371 pcs                                                          | Data sheet                     | <a href="#">30-00804 Drawing</a>                    |
| Category                                                                                                                                                                                                                                                                                                                                                                                                                                      | <a href="#">Cables, Wires</a>                                      | Wire Gauge                     | 24 AWG                                              |
| Voltage                                                                                                                                                                                                                                                                                                                                                                                                                                       | 300V                                                               | Usage                          | -                                                   |
| Shield Type                                                                                                                                                                                                                                                                                                                                                                                                                                   | -                                                                  | Shield Material                | -                                                   |
| Shield Coverage                                                                                                                                                                                                                                                                                                                                                                                                                               | -                                                                  | Series                         | -                                                   |
| Ratings                                                                                                                                                                                                                                                                                                                                                                                                                                       | UL Style 2651                                                      | Other Names                    | T1368-5                                             |
| Operating Temperature                                                                                                                                                                                                                                                                                                                                                                                                                         | -10°C ~ 105°C                                                      | Number of Conductors           | 2                                                   |
| Moisture Sensitivity Level (MSL)                                                                                                                                                                                                                                                                                                                                                                                                              | 1 (Unlimited)                                                      | Length                         | 16.40' (5.00m)                                      |
| Lead Free Status / RoHS Status                                                                                                                                                                                                                                                                                                                                                                                                                | Lead free / RoHS Compliant                                         | Jacket Color                   | Black, Red                                          |
| Jacket (Insulation) Thickness                                                                                                                                                                                                                                                                                                                                                                                                                 | 0.0165" (0.420mm)                                                  | Jacket (Insulation) Material   | Poly-Vinyl Chloride (PVC)                           |
| Jacket (Insulation) Diameter                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.118" (3.00mm)                                                    | Features                       | -                                                   |
| Detailed Description                                                                                                                                                                                                                                                                                                                                                                                                                          | 2 Conductor Multi-Conductor Cable Black, Red 24 AWG 16.40' (5.00m) | Conductor Strand               | 11/0.0063"                                          |
| Conductor Material                                                                                                                                                                                                                                                                                                                                                                                                                            | Copper, Tinned                                                     | Conductor Insulation           | -                                                   |
| Cable Type                                                                                                                                                                                                                                                                                                                                                                                                                                    | Multi-Conductor                                                    |                                |                                                     |
| Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Tensility International Corporation series electronic components. We have 14371 pieces of Tensility International Corporation 30-00804 in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours.<br>RFQ Email: info@Components-World.com |                                                                    |                                |                                                     |

| RELATED PRODUCTS                                                                   |                                                                                  |                                                                    |                |
|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|--------------------------------------------------------------------|----------------|
|  | Part#: <a href="#">30-00801</a><br>Description: CABLE 2COND 22AWG BLACK/RED 153M | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00807</a><br>Description: CABLE 2COND 26AWG BLACK/RED 153M | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00806</a><br>Description: CABLE 2COND 26AWG WHITE 153M     | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00809</a><br>Description: CABLE 2COND 28AWG WHITE 153M     | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00797</a><br>Description: CABLE 2COND 20AWG WHITE 153M     | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00808</a><br>Description: CBL 2CON 300V 28AWG BLK 5M       | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00801</a><br>Description: DRIVE RING 1/2'                  | Manufacturers: <a href="#">Belden</a>                              | <div>RFQ</div> |
|  | Part#: <a href="#">30-00796</a><br>Description: CBL 2CON 300V 20AWG BLK 1M       | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00810</a><br>Description: CABLE 2COND 28AWG BLACK/RED 153M | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00800</a><br>Description: CABLE 2COND 22AWG WHITE 153M     | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00805</a><br>Description: CBL 2CON 300V 26AWG BLK 5M       | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00872</a><br>Description: CBL 4CON 26/28AWG SHLD BLK 1M    | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00803</a><br>Description: CABLE 2COND 24AWG WHITE 153M     | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00805</a><br>Description: DRIVE RING 7/8'                  | Manufacturers: <a href="#">Belden</a>                              | <div>RFQ</div> |
|  | Part#: <a href="#">30-00804</a><br>Description: DRIVE RING 5/8'                  | Manufacturers: <a href="#">Belden</a>                              | <div>RFQ</div> |
|  | Part#: <a href="#">30-00798</a><br>Description: CABLE 2COND 20AWG BLACK/RED 153M | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00802</a><br>Description: CBL 2CON 300V 24AWG BLK 5M       | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00795</a><br>Description: CBL 2CON 18AWG RD/BLK 30M        | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00799</a><br>Description: CBL 2CON 300V 22AWG BLK 5M       | Manufacturers: <a href="#">Tensility International Corporation</a> | <div>RFQ</div> |
|  | Part#: <a href="#">30-00807</a><br>Description: DRIVE RING 1-1/4'                | Manufacturers: <a href="#">Belden</a>                              | <div>RFQ</div> |

Related keywords for 30-00804

|                                              |                                       |                   |                |
|----------------------------------------------|---------------------------------------|-------------------|----------------|
| Tensility International Corporation 30-00804 | 30-00804 distributor                  | 30-00804 supplier | 30-00804 price |
| 30-00804 download datasheet                  | 30-00804 datasheet                    | 30-00804 stock    | buy 30-00804   |
| Tensility International Corporation 30-00804 | Tensility International Corp 30-00804 |                   |                |