

3212 SL002





**Part Number:** 3212 SL002

**Manufacturer:** Alpha Wire

**Description:** CABLE 3COND 24AWG SHLD 500'

**Data sheet:**  [3212 Spec Sheet](#)  
 [Comm, Control, Industrial Cable Brochure](#)  
 [Part Number Ordering Guide](#)  
 [Comm, Control, Industrial Cable Catalog](#)

**RoHs Status:** Lead free / RoHS Compliant



**Ship From:** Hong Kong

**Shipment Way:** DHL/Fedex/TNT/UPS/EMS

Images are for reference only.  
See Product Specifications for product details.  
**Buy 3212 SL002 with confidence from Component-World.HK, 1 Year Warranty**

[Request For Quotation](#)

| PRODUCT PARAMETER                                                                                                                                                                                                                                                                                                                                                                                                                          |                               |                                 |                                                                                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Part Number                                                                                                                                                                                                                                                                                                                                                                                                                                | 3212 SL002                    | Manufacturer                    | <a href="#">Alpha Wire</a>                                                                                                                                                                           |
| Description                                                                                                                                                                                                                                                                                                                                                                                                                                | CABLE 3COND 24AWG SHLD 500'   | Lead Free Status / RoHS Status  | Lead free / RoHS Compliant                                                                                                                                                                           |
| Quantity Available                                                                                                                                                                                                                                                                                                                                                                                                                         | 127 pcs                       | Data sheet                      | <a href="#">3212 Spec Sheet</a><br><a href="#">Comm, Control, Industrial Cable Brochure</a><br><a href="#">Part Number Ordering Guide</a><br><a href="#">Comm, Control, Industrial Cable Catalog</a> |
| Category                                                                                                                                                                                                                                                                                                                                                                                                                                   | <a href="#">Cables, Wires</a> | Wire Gauge                      | 24 AWG                                                                                                                                                                                               |
| Voltage                                                                                                                                                                                                                                                                                                                                                                                                                                    | 600V                          | Usage                           | Communication, Control                                                                                                                                                                               |
| Shield Type                                                                                                                                                                                                                                                                                                                                                                                                                                | Braid                         | Shield Material                 | Copper, Tinned                                                                                                                                                                                       |
| Shield Coverage                                                                                                                                                                                                                                                                                                                                                                                                                            | 90%                           | Series                          | -                                                                                                                                                                                                    |
| Ratings                                                                                                                                                                                                                                                                                                                                                                                                                                    | -                             | Other Names                     | 3212 SL002-ND<br>3212SL002                                                                                                                                                                           |
| Operating Temperature                                                                                                                                                                                                                                                                                                                                                                                                                      | -55°C ~ 105°C                 | Number of Conductors            | 3                                                                                                                                                                                                    |
| Moisture Sensitivity Level (MSL)                                                                                                                                                                                                                                                                                                                                                                                                           | 1 (Unlimited)                 | Manufacturer Standard Lead Time | 6 Weeks                                                                                                                                                                                              |
| Length                                                                                                                                                                                                                                                                                                                                                                                                                                     | 500.0' (152.4m)               | Lead Free Status / RoHS Status  | Lead free / RoHS Compliant                                                                                                                                                                           |
| Jacket Color                                                                                                                                                                                                                                                                                                                                                                                                                               | Slate                         | Jacket (Insulation) Thickness   | 0.0160" (0.406mm)                                                                                                                                                                                    |
| Jacket (Insulation) Material                                                                                                                                                                                                                                                                                                                                                                                                               | Poly-Vinyl Chloride (PVC)     | Jacket (Insulation) Diameter    | 0.167" (4.24mm)                                                                                                                                                                                      |
| Features                                                                                                                                                                                                                                                                                                                                                                                                                                   | -                             | Detailed Description            | 3 Conductor Multi-Conductor Cable Slate 24 AWG Braid 500.0' (152.4m)                                                                                                                                 |
| Conductor Strand                                                                                                                                                                                                                                                                                                                                                                                                                           | 19/36                         | Conductor Material              | Copper, Tinned                                                                                                                                                                                       |
| Conductor Insulation                                                                                                                                                                                                                                                                                                                                                                                                                       | Poly-Vinyl Chloride (PVC)     | Cable Type                      | Multi-Conductor                                                                                                                                                                                      |
| Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Alpha Wire series electronic components. We have 127 pieces of Alpha Wire 3212 SL002 in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours.<br>RFQ Email: <a href="mailto:info@Components-World.com">info@Components-World.com</a> |                               |                                 |                                                                                                                                                                                                      |

| RELATED PRODUCTS                                                                   |                                                                                   |                                                                 |                     |
|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------|---------------------|
|  | Part#: <a href="#">3212</a><br>Description: WRENCH OPEN END 1-1/4" 16.63"         | Manufacturers: <a href="#">Klein Tools</a>                      | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3211993</a><br>Description: CONN TERM BLK FEED THRU 12-26AWG   | Manufacturers: <a href="#">Phoenix Contact</a>                  | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3211977</a><br>Description: TERM BLOCK PLUG 1POS 90DEG         | Manufacturers: <a href="#">Phoenix Contact</a>                  | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212</a><br>Description: TOOL LOCATOR STATIC SIZE 20           | Manufacturers: <a href="#">Astro Tool Corp.</a>                 | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212010</a><br>Description: TERM BLOCK PLUG 1POS 90DEG         | Manufacturers: <a href="#">Phoenix Contact</a>                  | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212002</a><br>Description: CONN TERM BLK FEED THRU 12-26AWG   | Manufacturers: <a href="#">Phoenix Contact</a>                  | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212-40002</a><br>Description: CONN SMPM PLUG R/A 50 OHM PCB   | Manufacturers: <a href="#">Amphenol SV Microwave</a>            | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212-40003-TD</a><br>Description: CONN SMPM PLUG R/A 50OHM PCB | Manufacturers: <a href="#">Amphenol SV Microwave</a>            | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3211980</a><br>Description: TERM BLOCK PLUG 1POS 90DEG         | Manufacturers: <a href="#">Phoenix Contact</a>                  | <a href="#">RFQ</a> |
|  | Part#: <a href="#">321201</a><br>Description: CONN RING CIRC 2AWG #1/4 CRIMP      | Manufacturers: <a href="#">Agastat Relays / TE Connectivity</a> | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212-40003</a><br>Description: CONN SMPM PLUG R/A 50 OHM PCB   | Manufacturers: <a href="#">Amphenol SV Microwave</a>            | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212-40002-TD</a><br>Description: CONN SMPM PLUG R/A 50OHM PCB | Manufacturers: <a href="#">Amphenol SV Microwave</a>            | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3211987</a><br>Description: TERM BLOCK PLUG 1POS 90DEG         | Manufacturers: <a href="#">Phoenix Contact</a>                  | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212007</a><br>Description: TERM BLK PLUG 2POS 6.2MM BLUE      | Manufacturers: <a href="#">Phoenix Contact</a>                  | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212</a><br>Description: WASHER FLAT #10 NYLON                 | Manufacturers: <a href="#">Keystone Electronics Corp.</a>       | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212</a><br>Description: BATT CHARGER 12V 1.5A X 2 UNIT        | Manufacturers: <a href="#">Patco Electronics</a>                | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212008</a><br>Description: TERM BLK PLUG 2POS 6.2MM ORANGE    | Manufacturers: <a href="#">Phoenix Contact</a>                  | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212 SL001</a><br>Description: CABLE 3COND 24AWG SHLD 1000'    | Manufacturers: <a href="#">Alpha Wire</a>                       | <a href="#">RFQ</a> |
|  | Part#: <a href="#">3212 SL005</a><br>Description: CABLE 3COND 24AWG SHLD 100'     | Manufacturers: <a href="#">Alpha Wire</a>                       | <a href="#">RFQ</a> |
|  | Part#: <a href="#">321198</a><br>Description: CONN SPLICE 22-26 AWG CRIMP         | Manufacturers: <a href="#">Agastat Relays / TE Connectivity</a> | <a href="#">RFQ</a> |

Related keywords for 3212 SL002

|                               |                        |                     |                  |
|-------------------------------|------------------------|---------------------|------------------|
| Alpha Wire 3212 SL002         | 3212 SL002 distributor | 3212 SL002 supplier | 3212 SL002 price |
| 3212 SL002 download datasheet | 3212 SL002 datasheet   | 3212 SL002 stock    | buy 3212 SL002   |
| Alpha Wire 3212 SL002         | Intel (CPU) 3212 SL002 |                     |                  |