

APSA4R0ELL271MFA5G





**Part Number:** [APSA4R0ELL271MFA5G](#)

**Manufacturer:** [Nippon Chemi-Con](#)

**Description:** CAP ALUM POLY 270UF 20% 4V T/H

**Data sheet:**  [PSA Series \(APSA\\_S/G\)](#)

**RoHs Status:** Lead free / RoHS Compliant



**Ship From:** Hong Kong

**Shipment Way:** DHL/Fedex/TNT/UPS/EMS

Images are for reference only.  
See Product Specifications for product details.  
**Buy APSA4R0ELL271MFA5G with confidence from Component-World.HK, 1 Year Warranty**

Request For Quotation

| PRODUCT PARAMETER                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                          |                                    |                                                 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|------------------------------------|-------------------------------------------------|
| Part Number                                                                                                                                                                                                                                                                                                                                                                                                                                                       | APSA4R0ELL271MFA5G                                                       | Manufacturer                       | <a href="#">Nippon Chemi-Con</a>                |
| Description                                                                                                                                                                                                                                                                                                                                                                                                                                                       | CAP ALUM POLY 270UF 20% 4V T/H                                           | Lead Free Status / RoHS Status     | Lead free / RoHS Compliant                      |
| Quantity Available                                                                                                                                                                                                                                                                                                                                                                                                                                                | 221765 pcs                                                               | Data sheet                         | <a href="#">PSA Series (APSA_S/G)</a>           |
| Category                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <a href="#">Capacitors</a>                                               | Voltage - Rated                    | 4V                                              |
| Type                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Polymer                                                                  | Tolerance                          | ±20%                                            |
| Surface Mount Land Size                                                                                                                                                                                                                                                                                                                                                                                                                                           | -                                                                        | Size / Dimension                   | 0.248" Dia (6.30mm)                             |
| Series                                                                                                                                                                                                                                                                                                                                                                                                                                                            | NPCAP™-PSA                                                               | Ripple Current @ High Frequency    | 3.16A @ 100kHz                                  |
| Ratings                                                                                                                                                                                                                                                                                                                                                                                                                                                           | -                                                                        | Packaging                          | Bulk                                            |
| Package / Case                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Radial, Can                                                              | Other Names                        | 565-3058<br>APSA4R0ELL271MF9JG<br>PSA4VB270MF11 |
| Operating Temperature                                                                                                                                                                                                                                                                                                                                                                                                                                             | -55°C ~ 105°C                                                            | Mounting Type                      | Through Hole                                    |
| Manufacturer Standard Lead Time                                                                                                                                                                                                                                                                                                                                                                                                                                   | 16 Weeks                                                                 | Lifetime @ Temp.                   | 2000 Hrs @ 105°C                                |
| Lead Spacing                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0.098" (2.50mm)                                                          | Lead Free Status / RoHS Status     | Lead free / RoHS Compliant                      |
| Height - Seated (Max)                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.413" (10.50mm)                                                         | ESR (Equivalent Series Resistance) | 20 mOhm                                         |
| Detailed Description                                                                                                                                                                                                                                                                                                                                                                                                                                              | 270μF 4V Aluminum Polymer Capacitor Radial, Can 20 mOhm 2000 Hrs @ 105°C | Capacitance                        | 270μF                                           |
| Applications                                                                                                                                                                                                                                                                                                                                                                                                                                                      | General Purpose                                                          |                                    |                                                 |
| Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Nippon Chemi-Con series electronic components. We have 221765 pieces of Nippon Chemi-Con APSA4R0ELL271MFA5G in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours.<br>RFQ Email: <a href="mailto:info@Components-World.com">info@Components-World.com</a> |                                                                          |                                    |                                                 |

| RELATED PRODUCTS                                                                  |                                                                                                |                                                 |                |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------|
|  | Part#: <a href="#">APSA4R0ELL391MFA5G</a><br><br>Description: CAP ALUM POLY 390UF 20% 4V T/H   | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA6R3ELL331MFA5G</a><br><br>Description: CAP ALUM POLY 330UF 20% 6.3V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA4R0ETD821MJB5S</a><br><br>Description: CAP ALUM POLY 820UF 20% 4V T/H   | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA100ETD151MFA5S</a><br><br>Description: CAP ALUM POLY 150UF 20% 10V T/H  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA6R3ELL681MJB5S</a><br><br>Description: CAP ALUM POLY 680UF 20% 6.3V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA2R5ELL391MFA5G</a><br><br>Description: CAP ALUM POLY 390UF 20% 2.5V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA160ELL101MFA5S</a><br><br>Description: CAP ALUM POLY 100UF 20% 16V T/H  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA4R0ELL561MHB5S</a><br><br>Description: CAP ALUM POLY 560UF 20% 4V T/H   | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA2R5ELL102MJB5S</a><br><br>Description: CAP ALUM POLY 1000UF 2.5V T/H    | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA100ETD470MFA5S</a><br><br>Description: CAP ALUM POLY 47UF 20% 10V T/H   | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA6R3ETD221MFA5G</a><br><br>Description: CAP ALUM POLY 220UF 20% 6.3V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA4R0ETD561MHB5S</a><br><br>Description: CAP ALUM POLY 560UF 20% 4V T/H   | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA6R3ELL391MHB5S</a><br><br>Description: CAP ALUM POLY 390UF 20% 6.3V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA4R0ELL821MJB5S</a><br><br>Description: CAP ALUM POLY 820UF 20% 4V T/H   | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA2R5ELL391MFA5S</a><br><br>Description: CAP ALUM POLY 390UF 20% 2.5V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA100ETD471MJB5S</a><br><br>Description: CAP ALUM POLY 470UF 20% 10V T/H  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA2R5ELL681MHB5S</a><br><br>Description: CAP ALUM POLY 680UF 20% 2.5V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA2R5ELL821MHB5S</a><br><br>Description: CAP ALUM POLY 820UF 20% 2.5V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA6R3ELL221MFA5G</a><br><br>Description: CAP ALUM POLY 220UF 20% 6.3V T/H | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">APSA160ELL101MFA5G</a><br><br>Description: CAP ALUM POLY 100UF 20% 16V T/H  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |

|                                                |                                     |                             |                          |
|------------------------------------------------|-------------------------------------|-----------------------------|--------------------------|
| Related keywords for <b>APSA4R0ELL271MFA5G</b> |                                     |                             |                          |
| Nippon Chemi-Con APSA4R0ELL271MFA5G            | APSA4R0ELL271MFA5G distributor      | APSA4R0ELL271MFA5G supplier | APSA4R0ELL271MFA5G price |
| APSA4R0ELL271MFA5G download datasheet          | APSA4R0ELL271MFA5G datasheet        | APSA4R0ELL271MFA5G stock    | buy APSA4R0ELL271MFA5G   |
| Nippon Chemi-Con APSA4R0ELL271MFA5G            | United Chemi-Con APSA4R0ELL271MFA5G |                             |                          |