

E37X401CPN562MF92M





**Part Number:** [E37X401CPN562MF92M](#)

**Manufacturer:** [Nippon Chemi-Con](#)

**Description:** CAP ALUM 5600UF 20% 400V SCREW

**Data sheet:**  [U37X Series](#)

**RoHs Status:** Lead free / RoHS Compliant

**Ship From:** Hong Kong

**Shipment Way:** DHL/Fedex/TNT/UPS/EMS

Images are for reference only.  
See Product Specifications for product details.  
Buy E37X401CPN562MF92M with confidence from  
Component-World.HK, 1 Year Warranty

Request For Quotation

| PRODUCT PARAMETER                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                |                                 |                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|---------------------------------|-------------------------------------------------------------------------------------------------------------|
| Part Number                                                                                                                                                                                                                                                                                                                                                                                                                                                     | E37X401CPN562MF92M             | Manufacturer                    | <a href="#">Nippon Chemi-Con</a>                                                                            |
| Description                                                                                                                                                                                                                                                                                                                                                                                                                                                     | CAP ALUM 5600UF 20% 400V SCREW | Lead Free Status / RoHS Status  | Lead free / RoHS Compliant                                                                                  |
| Quantity Available                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1252 pcs                       | Data sheet                      | <a href="#">U37X Series</a>                                                                                 |
| Category                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <a href="#">Capacitors</a>     | Voltage - Rated                 | 400V                                                                                                        |
| Tolerance                                                                                                                                                                                                                                                                                                                                                                                                                                                       | ±20%                           | Surface Mount Land Size         | -                                                                                                           |
| Size / Dimension                                                                                                                                                                                                                                                                                                                                                                                                                                                | 3.504" Dia (89.00mm)           | Series                          | U37X                                                                                                        |
| Ripple Current @ Low Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                  | 15.1A @ 120Hz                  | Ripple Current @ High Frequency | 42.441A @ 10kHz                                                                                             |
| Ratings                                                                                                                                                                                                                                                                                                                                                                                                                                                         | -                              | Polarization                    | Polar                                                                                                       |
| Packaging                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Bulk                           | Package / Case                  | Radial, Can - Screw Terminals                                                                               |
| Operating Temperature                                                                                                                                                                                                                                                                                                                                                                                                                                           | -40°C ~ 85°C                   | Mounting Type                   | Chassis Mount                                                                                               |
| Moisture Sensitivity Level (MSL)                                                                                                                                                                                                                                                                                                                                                                                                                                | 1 (Unlimited)                  | Manufacturer Standard Lead Time | 16 Weeks                                                                                                    |
| Lifetime @ Temp.                                                                                                                                                                                                                                                                                                                                                                                                                                                | 15000 Hrs @ 85°C               | Lead Spacing                    | 1.250" (31.75mm)                                                                                            |
| Lead Free Status / RoHS Status                                                                                                                                                                                                                                                                                                                                                                                                                                  | Lead free / RoHS Compliant     | Height - Seated (Max)           | 3.661" (93.00mm)                                                                                            |
| ESR (Equivalent Series Resistance)                                                                                                                                                                                                                                                                                                                                                                                                                              | 22 mOhm @ 120Hz                | Detailed Description            | 5600µF 400V Aluminum Electrolytic Capacitors Radial, Can - Screw Terminals 22 mOhm @ 120Hz 15000 Hrs @ 85°C |
| Capacitance                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 5600µF                         | Applications                    | General Purpose                                                                                             |
| Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Nippon Chemi-Con series electronic components. We have 1252 pieces of Nippon Chemi-Con E37X401CPN562MF92M in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours.<br>RFQ Email: <a href="mailto:info@Components-World.com">info@Components-World.com</a> |                                |                                 |                                                                                                             |

| RELATED PRODUCTS                                                                   |                                                                                           |                                                 |                |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------|----------------|
|  | Part#: <a href="#">E37X401CPN682MFA5M</a><br>Description: CAP ALUM 6800UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN272MD92M</a><br>Description: CAP ALUM 2700UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN682MFB7M</a><br>Description: CAP ALUM 6800UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN153MFM9M</a><br>Description: CAP ALUM 15000UF 20% 400V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN103MEM9M</a><br>Description: CAP ALUM 10000UF 20% 420V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN392MDD0M</a><br>Description: CAP ALUM 3900UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN272MDA5M</a><br>Description: CAP ALUM 2700UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN682MEE3M</a><br>Description: CAP ALUM 6800UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN562MEB7M</a><br>Description: CAP ALUM 5600UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN822MEJ1M</a><br>Description: CAP ALUM 8200UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN153MFM9M</a><br>Description: CAP ALUM 15000UF 20% 420V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401HPN272MCD0M</a><br>Description: CAP ALUM 2700UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN392MDE3M</a><br>Description: CAP ALUM 3900UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401HPN272MCB7M</a><br>Description: CAP ALUM 2700UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN123MFK0M</a><br>Description: CAP ALUM 12000UF 20% 400V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN472MEA5M</a><br>Description: CAP ALUM 4700UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN392ME92M</a><br>Description: CAP ALUM 3900UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN103MFF5M</a><br>Description: CAP ALUM 10000UF 20% 420V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN332MDB7M</a><br>Description: CAP ALUM 3300UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN123MFK0M</a><br>Description: CAP ALUM 12000UF 20% 420V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |

Related keywords for E37X401CPN562MF92M

|                                       |                                     |                             |                          |
|---------------------------------------|-------------------------------------|-----------------------------|--------------------------|
| Nippon Chemi-Con E37X401CPN562MF92M   | E37X401CPN562MF92M distributor      | E37X401CPN562MF92M supplier | E37X401CPN562MF92M price |
| E37X401CPN562MF92M download datasheet | E37X401CPN562MF92M datasheet        | E37X401CPN562MF92M stock    | buy E37X401CPN562MF92M   |
| Nippon Chemi-Con E37X401CPN562MF92M   | United Chemi-Con E37X401CPN562MF92M |                             |                          |