

E37X421CPN153MFM9M





**Part Number:** [E37X421CPN153MFM9M](#)

**Manufacturer:** [Nippon Chemi-Con](#)

**Description:** CAP ALUM 15000UF 20% 420V SCREW

**Data sheet:**  [U37X Series](#)

**RoHs Status:** Lead free / RoHS Compliant

**Ship From:** Hong Kong

**Shipment Way:** DHL/Fedex/TNT/UPS/EMS

Images are for reference only.  
See Product Specifications for product details.  
Buy E37X421CPN153MFM9M with confidence from  
Component-World.HK, 1 Year Warranty

Request For Quotation

| PRODUCT PARAMETER                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                 |                                 |                                                                                                             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|---------------------------------|-------------------------------------------------------------------------------------------------------------|
| Part Number                                                                                                                                                                                                                                                                                                                                                                                                                                                    | E37X421CPN153MFM9M              | Manufacturer                    | <a href="#">Nippon Chemi-Con</a>                                                                            |
| Description                                                                                                                                                                                                                                                                                                                                                                                                                                                    | CAP ALUM 15000UF 20% 420V SCREW | Lead Free Status / RoHS Status  | Lead free / RoHS Compliant                                                                                  |
| Quantity Available                                                                                                                                                                                                                                                                                                                                                                                                                                             | 755 pcs                         | Data sheet                      | <a href="#">U37X Series</a>                                                                                 |
| Category                                                                                                                                                                                                                                                                                                                                                                                                                                                       | <a href="#">Capacitors</a>      | Voltage - Rated                 | 420V                                                                                                        |
| Tolerance                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ±20%                            | Surface Mount Land Size         | -                                                                                                           |
| Size / Dimension                                                                                                                                                                                                                                                                                                                                                                                                                                               | 3.504" Dia (89.00mm)            | Series                          | U37X                                                                                                        |
| Ripple Current @ Low Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                 | 34A @ 120Hz                     | Ripple Current @ High Frequency | 47.94A @ 10kHz                                                                                              |
| Ratings                                                                                                                                                                                                                                                                                                                                                                                                                                                        | -                               | Polarization                    | Polar                                                                                                       |
| Packaging                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Bulk                            | Package / Case                  | Radial, Can - Screw Terminals                                                                               |
| Operating Temperature                                                                                                                                                                                                                                                                                                                                                                                                                                          | -40°C ~ 85°C                    | Mounting Type                   | Chassis Mount                                                                                               |
| Moisture Sensitivity Level (MSL)                                                                                                                                                                                                                                                                                                                                                                                                                               | 1 (Unlimited)                   | Manufacturer Standard Lead Time | 16 Weeks                                                                                                    |
| Lifetime @ Temp.                                                                                                                                                                                                                                                                                                                                                                                                                                               | 15000 Hrs @ 85°C                | Lead Spacing                    | 1.252" (31.80mm)                                                                                            |
| Lead Free Status / RoHS Status                                                                                                                                                                                                                                                                                                                                                                                                                                 | Lead free / RoHS Compliant      | Height - Seated (Max)           | 8.661" (220.00mm)                                                                                           |
| ESR (Equivalent Series Resistance)                                                                                                                                                                                                                                                                                                                                                                                                                             | 8 mOhm @ 120Hz                  | Detailed Description            | 15000µF 420V Aluminum Electrolytic Capacitors Radial, Can - Screw Terminals 8 mOhm @ 120Hz 15000 Hrs @ 85°C |
| Capacitance                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 15000µF                         | Applications                    | General Purpose                                                                                             |
| Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Nippon Chemi-Con series electronic components. We have 755 pieces of Nippon Chemi-Con E37X421CPN153MFM9M in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours.<br>RFQ Email: <a href="mailto:info@Components-World.com">info@Components-World.com</a> |                                 |                                 |                                                                                                             |

| RELATED PRODUCTS                                                                   |                                                                                           |                                                 |                |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------|----------------|
|  | Part#: <a href="#">E37X401CPN682MEE3M</a><br>Description: CAP ALUM 6800UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN392MDE3M</a><br>Description: CAP ALUM 3900UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN562MF92M</a><br>Description: CAP ALUM 5600UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN472MF92M</a><br>Description: CAP ALUM 4700UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN332MDB7M</a><br>Description: CAP ALUM 3300UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN103MEM9M</a><br>Description: CAP ALUM 10000UF 20% 420V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN822MEJ1M</a><br>Description: CAP ALUM 8200UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN123MFK0M</a><br>Description: CAP ALUM 12000UF 20% 420V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401HPN272MCB7M</a><br>Description: CAP ALUM 2700UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN392MDD0M</a><br>Description: CAP ALUM 3900UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN682MFB7M</a><br>Description: CAP ALUM 6800UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN103MFF5M</a><br>Description: CAP ALUM 10000UF 20% 420V SCREW | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN562MEE3M</a><br>Description: CAP ALUM 5600UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401HPN272MCD0M</a><br>Description: CAP ALUM 2700UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN392MEA5M</a><br>Description: CAP ALUM 3900UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN472MEB7M</a><br>Description: CAP ALUM 4700UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X401CPN682MFA5M</a><br>Description: CAP ALUM 6800UF 20% 400V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN222MD92M</a><br>Description: CAP ALUM 2200UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN332ME92M</a><br>Description: CAP ALUM 3300UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">E37X421CPN272MDA5M</a><br>Description: CAP ALUM 2700UF 20% 420V SCREW  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |

| Related keywords for E37X421CPN153MFM9M |                                     |                             |                          |
|-----------------------------------------|-------------------------------------|-----------------------------|--------------------------|
| Nippon Chemi-Con E37X421CPN153MFM9M     | E37X421CPN153MFM9M distributor      | E37X421CPN153MFM9M supplier | E37X421CPN153MFM9M price |
| E37X421CPN153MFM9M download datasheet   | E37X421CPN153MFM9M datasheet        | E37X421CPN153MFM9M stock    | buy E37X421CPN153MFM9M   |
| Nippon Chemi-Con E37X421CPN153MFM9M     | United Chemi-Con E37X421CPN153MFM9M |                             |                          |