

EFL-250ELL150MD07D





**Part Number:** [EFL-250ELL150MD07D](#)

**Manufacturer:** [Nippon Chemi-Con](#)

**Description:** CAP ALUM 15UF 20% 25V THRU HOLE

**Data sheet:**  [FL Series](#)

**RoHs Status:** Lead free / RoHS Compliant

**Ship From:** Hong Kong

**Shipment Way:** DHL/Fedex/TNT/UPS/EMS

Images are for reference only.  
See Product Specifications for product details.  
Buy EFL-250ELL150MD07D with confidence from  
Component-World.HK, 1 Year Warranty

Request For Quotation

| PRODUCT PARAMETER                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                 |                                  |                                                                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|----------------------------------|------------------------------------------------------------------------|
| Part Number                                                                                                                                                                                                                                                                                                                                                                                                                                                       | EFL-250ELL150MD07D              | Manufacturer                     | <a href="#">Nippon Chemi-Con</a>                                       |
| Description                                                                                                                                                                                                                                                                                                                                                                                                                                                       | CAP ALUM 15UF 20% 25V THRU HOLE | Lead Free Status / RoHS Status   | Lead free / RoHS Compliant                                             |
| Quantity Available                                                                                                                                                                                                                                                                                                                                                                                                                                                | 821805 pcs                      | Data sheet                       | <a href="#">FL Series</a>                                              |
| Category                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <a href="#">Capacitors</a>      | Voltage - Rated                  | 25V                                                                    |
| Tolerance                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ±20%                            | Surface Mount Land Size          | -                                                                      |
| Size / Dimension                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.157" Dia (4.00mm)             | Series                           | FL                                                                     |
| Ripple Current @ Low Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                    | 17.6mA @ 120Hz                  | Ripple Current @ High Frequency  | 44mA @ 100kHz                                                          |
| Ratings                                                                                                                                                                                                                                                                                                                                                                                                                                                           | -                               | Polarization                     | Polar                                                                  |
| Packaging                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Bulk                            | Package / Case                   | Radial, Can                                                            |
| Other Names                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 565-4399                        | Operating Temperature            | -40°C ~ 105°C                                                          |
| Mounting Type                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Through Hole                    | Moisture Sensitivity Level (MSL) | 1 (Unlimited)                                                          |
| Manufacturer Standard Lead Time                                                                                                                                                                                                                                                                                                                                                                                                                                   | 16 Weeks                        | Lifetime @ Temp.                 | 3000 Hrs @ 105°C                                                       |
| Lead Spacing                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0.059" (1.50mm)                 | Lead Free Status / RoHS Status   | Lead free / RoHS Compliant                                             |
| Impedance                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 4.5 Ohms                        | Height - Seated (Max)            | 0.315" (8.00mm)                                                        |
| ESR (Equivalent Series Resistance)                                                                                                                                                                                                                                                                                                                                                                                                                                | -                               | Detailed Description             | 15µF 25V Aluminum Electrolytic Capacitors Radial, Can 3000 Hrs @ 105°C |
| Capacitance                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 15µF                            | Applications                     | General Purpose                                                        |
| Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Nippon Chemi-Con series electronic components. We have 821805 pieces of Nippon Chemi-Con EFL-250ELL150MD07D in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours.<br>RFQ Email: <a href="mailto:info@Components-World.com">info@Components-World.com</a> |                                 |                                  |                                                                        |

| RELATED PRODUCTS                                                                   |                                                                                            |                                                 |                |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------|----------------|
|  | Part#: <a href="#">EFL-160ELL150MD05D</a><br>Description: CAP ALUM 15UF 20% 16V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-160ELL220MD07D</a><br>Description: CAP ALUM 22UF 20% 16V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-350ELL330MH05G</a><br>Description: CAP ALUM 33UF 20% 35V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-250ELL330MF05D</a><br>Description: CAP ALUM 33UF 20% 25V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-160ELL680MF07D</a><br>Description: CAP ALUM 68UF 20% 16V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-250ELL680MH05G</a><br>Description: CAP ALUM 68UF 20% 25V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-250ELL220ME07D</a><br>Description: CAP ALUM 22UF 20% 25V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-350ELL220MF05D</a><br>Description: CAP ALUM 22UF 20% 35V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-160ELL101MH05G</a><br>Description: CAP ALUM 100UF 20% 16V THRU HOLE | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-350ELL220MF07D</a><br>Description: CAP ALUM 22UF 20% 35V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-350ELL100ME05D</a><br>Description: CAP ALUM 10UF 20% 35V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-250ELL560MF07D</a><br>Description: CAP ALUM 56UF 20% 25V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-250ELL101MH07D</a><br>Description: CAP ALUM 100UF 20% 25V THRU HOLE | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-250ELL100MD05D</a><br>Description: CAP ALUM 10UF 20% 25V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-160ELL220ME05D</a><br>Description: CAP ALUM 22UF 20% 16V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-250ELL150ME05D</a><br>Description: CAP ALUM 15UF 20% 25V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-350ELL100ME07D</a><br>Description: CAP ALUM 10UF 20% 35V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-160ELL151MH07D</a><br>Description: CAP ALUM 150UF 20% 16V THRU HOLE | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-160ELL330ME07D</a><br>Description: CAP ALUM 33UF 20% 16V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |
|  | Part#: <a href="#">EFL-160ELL470MF05D</a><br>Description: CAP ALUM 47UF 20% 16V THRU HOLE  | Manufacturers: <a href="#">Nippon Chemi-Con</a> | <div>RFQ</div> |

| Related keywords for EFL-250ELL150MD07D |                                     |                             |                          |
|-----------------------------------------|-------------------------------------|-----------------------------|--------------------------|
| Nippon Chemi-Con EFL-250ELL150MD07D     | EFL-250ELL150MD07D distributor      | EFL-250ELL150MD07D supplier | EFL-250ELL150MD07D price |
| EFL-250ELL150MD07D download datasheet   | EFL-250ELL150MD07D datasheet        | EFL-250ELL150MD07D stock    | buy EFL-250ELL150MD07D   |
| Nippon Chemi-Con EFL-250ELL150MD07D     | United Chemi-Con EFL-250ELL150MD07D |                             |                          |