

Images are for reference only. See Product Specifications for product details. Buy FGN0.25BK50 with confidence from Component-World.HK, 1 Year Warranty

FGN0.25BK50

Part Number: FGN0.25BK50 **Manufacturer Techflex Description** SLEEVING 1/4" X 50' BLACK Data sheet: Insultherm™ Catalog Page

Insultherm™ Datasheet

RoHs Status: Lead free / RoHS Compliant

Ship From: Hong Kong

Shipment Way: DHL/Fedex/TNT/UPS/EMS

Request For Quotation

PRODUCT PARAMETER			
Part Number	FGN0.25BK50	Manufacturer	Techflex
Description	SLEEVING 1/4" X 50' BLACK	Lead Free Status / RoHS Status	Lead free / RoHS Compliant
Quantity Available	2689 pcs	Data sheet	Insultherm™ Catalog Page Insultherm™ Datasheet
Category	Cables, Wires - Management	Width	-
Wall Thickness	0.031" (0.79mm)	Type Attributes	Expandable
Туре	Sleeving	Series	Insultherm®
Other Names	1030-1111 FGN025BK50	Operating Temperature	-70°C ~ 650°C
Moisture Sensitivity Level (MSL)	1 (Unlimited)	Material Flammability Rating	UL VW-1
Material	Fiberglass, Resin Coated, Halogen Free	Manufacturer Standard Lead Time	5 Weeks
Liquid Protection	Gasoline Resistant	Length	50.00' (15.24m)
Lead Free Status / RoHS Status	Lead free / RoHS Compliant	Heat Protection	Heat Resistant
Features	Chemical Resistant, Clean Cut, Vibration Resistant	Environment Protection	-
Diameter - Outside, Non-Expanded	-	Diameter - Inside, Non-Expanded	0.250" (6.35mm)
Diameter - Inside, Expanded	0.375" (9.52mm)	Color	Black
Abrasion Protection	Abrasion and Cut Resistant		
	ibutor of Electronic Components. We specialize in all Techflex series extributor at Component-World.com, our sales team will contact you within		FGN0.25BK50 in stock available now.

Wall Thic	ckness	0.031" (0.79mm)		Type Attributes	Expandable
Туре		Sleeving		Series	Insultherm®
Other Na	ames	1030-1111			-70°C ~ 650°C
		FGN025BK50		Operating Temperature	·····
Moisture	e Sensitivity Level (MSL)	1 (Unlimited)	_	Material Flammability Rating	UL VW-1
Material		Fiberglass, Resin Coated, Haloç	gen Free	Manufacturer Standard Lead Time	5 Weeks
Liquid Pr	rotection	Gasoline Resistant		Length	50.00' (15.24m)
					······
Lead Fre	ee Status / RoHS Status	Lead free / RoHS Compliant		Heat Protection	Heat Resistant
Features	3	Chemical Resistant, Clean Cut,	Vibration Resistant	Environment Protection	-
Diameter	r - Outside, Non-Expanded	-		Diameter - Inside, Non-Expanded	0.250" (6.35mm)
		0 275" (0 52mm)			
	r - Inside, Expanded	0.375" (9.52mm)		Color	Black
Abrasion	n Protection	Abrasion and Cut Resistant			
quest a quot	_	stributor of Electronic Components. We sp stributor at Component-World.com, our sa		c components. We have 2689 pieces of Techflex rs.	FGN0.25BK50 in stock available now
RELATED	PRODUCTS				
	Part#: FGN.FF.304.YLC		Manufacturers: LEMO		
LEMO.					RFQ
he Original Push Pull Connector	Description: CONN PLUG MAL	E 4POS GOLD CRIMP			
	Deville FOLIO				
	Part#: FGN0.50BK		Manufacturers: Techflex		RFQ
	Description: SLEEVING 1/2" X	200' BLACK			KFQ
all	2000 PAON GELEVING 1/2 A				
Ro.	Part#: FGN0.75BK		Manufacturers: Techflex		
					RFQ
199	Description: SLEEVING 3/4" X	200' BLACK			
*					
	Part#: FGN.3F.330.XLCF		Manufacturers: LEMO		
- = III	TORIOI JOULALOF		Managadi Gis. LEWO		RFQ
Original Push Pull Connector	Description: CONN INLINE PL	UG			
	Part#: FGN0.38SV		Manufacturers: Techflex		RFQ
	Description: SLEEVING 3/8" X	200' SILVER			1113
	, , C	•			
	Part#: FGN.FF.303.YLC		Manufacturers: LEMO		
Original Push-Pull Connector					RFQ
	Description: CONN PLUG MAL	E 3POS GOLD CRIMP			
	Part# ECNO 750K50		Manufacturers: Techflex		
	Part#: FGN0.75BK50		ivianulacturers: Techflex		RFQ
THE PERSON NAMED IN COLUMN TO PERSON NAMED I	Description: SLEEVING 3/4" X	50' BLACK			
	Part#: FGN.3F.330.CLC		Manufacturers: LEMO		RFQ
e Original Push-Pull Connector	Description: CONN PLUG MAL	E 30POS GOLD CRIMP			RFQ
	DOSCIPTION. CONN FLUG WAL	LE CO. CO COLD CIMIVII			
	Part#: FGN.3M.330.XLCM		Manufacturers: LEMO		
LETTO . Original Push Pull Connector					RFQ
	Description: CONN INLINE PLI	UG			
	Part# ECNIC 20DIZEC		Manufacturers: Techflex		
	Part#: FGN0.38BK50		ivianulacturers: Techflex		RFQ
	Description: SLEEVING 3/8" X	50' BLACK			
	Part#: FGN0.50BK50		Manufacturers: Techflex		
	D	FOLDI ACI			RFQ
Of the second	Description: SLEEVING 1/2" X	50' BLACK			
	Part#: FGN0.38BK		Manufacturers: Techflex		
			- Tooliio		RFQ
	Description: SLEEVING 3/8" X	200' BLACK			
	Dartille CONO CODICEO		Manufact		
	Part#: FGN0.63BK50		Manufacturers: Techflex		RFQ
	Description: SLEEVING 5/8" X	50' BLACK			
	,				
	Part#: FGN0.63BK		Manufacturers: Techflex		
					RFQ
	Description: SLEEVING 5/8" X	200' BLACK			
100					
•			Manufacturers		
_	Part# ECM 2M 220 VLOT		Manufacturers: LEMO		
.eme	Part#: FGN.3M.330.XLCT				RFQ
Original Push Pull Connector	Part#: FGN.3M.330.XLCT Description: CONN PLUG MAL	E 30POS GOLD CRIMP			RFQ
Original Push-Pull Connection		E 30POS GOLD CRIMP	<u></u>		RFQ
Original Push Pull Connector		E 30POS GOLD CRIMP	<u>-</u>		RFQ
Organial Productive Commenction		E 30POS GOLD CRIMP	Manufacturers: Techflex		
Corgonal Push Pull Guernacher	Description: CONN PLUG MAL Part#: FGN0.25BK		Manufacturers: Techflex		RFQ
a Organal Push Pull Connection	Description: CONN PLUG MAL		Manufacturers: Techflex		
LEMD, the Original Push Pull Connection	Description: CONN PLUG MAL Part#: FGN0.25BK		Manufacturers: Techflex		

Part#: FGN.MM.304.XLCT Manufacturers: LEMO RFQ L. LEMD. Description: CONN INLINE PLUG

Part#: FGN1.00BK Manufacturers: Techflex RFQ Description: SLEEVING 1" X 100' BLACK

Part#: FGN.3F.330.XLCS Manufacturers: LEMO RFQ L. LEMO. Description: CONN PLUG MALE 30POS GOLD CRIMP

Manufacturers: LEMO

FGN0.25BK50 stock

Related keywords for FGN0.25BK50 Techflex FGN0.25BK50 FGN0.25BK50 supplier FGN0.25BK50 price FGN0.25BK50 distributor

buy FGN0.25BK50







RFQ

FGN0.25BK50 datasheet

Part#: FGN.3F.330.XLC

FGN0.25BK50 download datasheet

Techflex FGN0.25BK50

Description: CONN PLUG MALE 30POS GOLD CRIMP

L. LEMO.