

HST0.4-48-5-2Y



**Part Number:** [HST0.4-48-5-2Y](#)

**Manufacturer:** [Panduit](#)

**Description:** HEAT SHRINK THICK ADH RED

**Data sheet:**  [HST Installation Instructions](#)  
 [HST Series Drawing](#)  
 [Polyolefin Heat Shrink Spec Sheet](#)  
 [Thick Wall Polyolefin Heat Shrink CutSheet](#)

**RoHs Status:** Lead free / RoHS Compliant

**Ship From:** Hong Kong


**Shipment Way:** DHL/Fedex/TNT/UPS/EMS

Images are for reference only.  
See Product Specifications for product details.  
Buy HST0.4-48-5-2Y with confidence from Component-World.HK, 1 Year Warranty

Request For Quotation

| PRODUCT PARAMETER                |                                                                          |                                |                                                                                                                                                                                                        |
|----------------------------------|--------------------------------------------------------------------------|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Part Number                      | HST0.4-48-5-2Y                                                           | Manufacturer                   | <a href="#">Panduit</a>                                                                                                                                                                                |
| Description                      | HEAT SHRINK THICK ADH RED                                                | Lead Free Status / RoHS Status | Lead free / RoHS Compliant                                                                                                                                                                             |
| Quantity Available               | 3237 pcs                                                                 | Data sheet                     | <a href="#">HST Installation Instructions</a><br><a href="#">HST Series Drawing</a><br><a href="#">Polyolefin Heat Shrink Spec Sheet</a><br><a href="#">Thick Wall Polyolefin Heat Shrink CutSheet</a> |
| Category                         | <a href="#">Cables, Wires - Management</a>                               | Type                           | Tubing, Semi Rigid                                                                                                                                                                                     |
| Shrinkage Ratio                  | 3 to 1                                                                   | Shrink Temperature             | 120°C                                                                                                                                                                                                  |
| Series                           | HST                                                                      | Recovered Wall Thickness       | 0.080" (2.03mm)                                                                                                                                                                                        |
| Other Names                      | 07498310711<br>298-13377<br>HST0.4-48-5-2Y-ND                            | Operating Temperature          | -65°C ~ 110°C                                                                                                                                                                                          |
| Moisture Sensitivity Level (MSL) | Not Applicable                                                           | Material                       | Polyolefin (PO), Irradiated                                                                                                                                                                            |
| Manufacturer Standard Lead Time  | 4 Weeks                                                                  | Length                         | 4.00' (1.22m)                                                                                                                                                                                          |
| Lead Free Status / RoHS Status   | Lead free / RoHS Compliant                                               | Inner Diameter - Supplied      | 0.400" (10.16mm)                                                                                                                                                                                       |
| Inner Diameter - Recovered       | 0.160" (4.06mm)                                                          | Features                       | Adhesive Lined, Flame Retardant                                                                                                                                                                        |
| Detailed Description             | Heat Shrink Tubing, Semi Rigid 0.400" (10.16mm) 3 to 1 Red 4.00' (1.22m) | Color                          | Red                                                                                                                                                                                                    |

Component-World.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Panduit series electronic components. We have 3237 pieces of Panduit HST0.4-48-5-2Y in stock available now. Request a quote from electronics components distributor at Component-World.com, our sales team will contact you within 24 hours.  
RFQ Email: [info@Components-World.com](mailto:info@Components-World.com)

| RELATED PRODUCTS                                                                   |                                                                                       |                                        |                |
|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|----------------|
|  | Part#: <a href="#">HST0.8-48-5-2Y</a><br>Description: HEAT SHRINK THICK ADH RED       | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.8-12-5-2</a><br>Description: HEAT SHRINK THICK ADH RED .8X12" | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-6-X2</a><br>Description: HEAT SHRINK THICK ADH RED .4X6"    | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.8-12-5</a><br>Description: HEAT SHRINK THICK ADH BLK .8X12"   | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-3-Q2Y</a><br>Description: HEAT SHRINK THICK ADH RED         | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.8-6-3</a><br>Description: HEAT SHRINK THICK WALL .8"X6"       | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.8-48-5Y</a><br>Description: HEAT SHRINK THICK ADH BLK .8"X4'  | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-3-QY</a><br>Description: HEAT SHRINK THICK ADH BLACK        | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-6-3</a><br>Description: HEAT SHRINK THICK WALL .4"X6"       | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.8-12-5Y</a><br>Description: HEAT SHRINK THICK ADH BLACK       | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.8-12-5-2Y</a><br>Description: HEAT SHRINK THICK ADH RED       | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-6-XY</a><br>Description: HEAT SHRINK THICK ADH BLACK        | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-48-5-2</a><br>Description: HEAT SHRINK THICK ADH RED .4"X4' | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-6-X</a><br>Description: HEAT SHRINK THICK ADH BLK .4X6"     | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.8-48-5-2</a><br>Description: HEAT SHRINK THICK ADH RED .8"X4' | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-6-3Y</a><br>Description: HEAT SHRINK THICK ADH BLACK        | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-3-Q2</a><br>Description: HEAT SHRINK THICK ADH RED .4X3"    | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-48-5Y</a><br>Description: HEAT SHRINK THICK ADH BLK .4"X4'  | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-3-Q</a><br>Description: HEAT SHRINK THICK ADH BLK .4X3"     | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |
|  | Part#: <a href="#">HST0.4-6-X2Y</a><br>Description: HEAT SHRINK THICK ADH RED         | Manufacturers: <a href="#">Panduit</a> | <div>RFQ</div> |

| Related keywords for HST0.4-48-5-2Y |                             |                         |                      |
|-------------------------------------|-----------------------------|-------------------------|----------------------|
| Panduit HST0.4-48-5-2Y              | HST0.4-48-5-2Y distributor  | HST0.4-48-5-2Y supplier | HST0.4-48-5-2Y price |
| HST0.4-48-5-2Y download datasheet   | HST0.4-48-5-2Y datasheet    | HST0.4-48-5-2Y stock    | buy HST0.4-48-5-2Y   |
| Panduit HST0.4-48-5-2Y              | Panduit Corp HST0.4-48-5-2Y |                         |                      |